

B086 KIT CLEVELAND OPEN CAP FLASH AND FIRE POINT TESTER

STANDARDS: EN 22592 | ASTM D92 | AASHTO T48
IP 36 | NF T60-118 | ISO 2592

Used to measure the flash and fire points of lubricated oils and petroleum products.

Complete with brass cup, thermometer IP 28C (ASTM 11C) range -6 +400 °C, electric heater with thermoregulator, double line fuse. Supplied **without** flame gas device to be ordered separately.

Power supply: 230V 1ph 50-60Hz 600W

Dimensions: 220x285x265 mm approx.

Weight: 10 kg approx.

NEEDED ACCESSORY

B086-02

FLAME GAS device, complete with gas-stop valve controlled by a flame sensor and maximum thermostat with reset button. It can be sold in CE markets, but not usable in closed spaces.

SPARE

B086-10 Thermometer IP 28C (ASTM 11C), range -6 +400 °C.

B087

SAYBOLT DIGITAL VISCOMETER

STANDARDS: ASTM D88 | AASHTO T72

Used to determine the viscosity of petroleum products at specified temperatures between 70 to 210 °F. Stainless steel made, the Saybolt viscometer is supplied complete with two interchangeable orifices **Furol** and **Universal**, oil bath, electric heater with digital thermoregulator, stirrer, cooling coil, viscosity flask. Thermometers, filter funnel, withdrawal tube **are not included** and must be ordered separately. The viscometer is equipped of a dual safety thermostat to prevent accidental over-heatings.

Power supply: 230V 1ph 50-60Hz 500W

Dimensions: 280x260x510 mm

Weight: 12 kg approx.

ACCESSORIES

Saybolt Thermometers	Range	Subd.
B089 ASTM 17C	+19 a +27 °C	0.1 °C
B089-01 ASTM 18C	+34 a +42 °C	0.1 °C
B089-02 ASTM 19C	+49 a +57 °C	0.1 °C
B089-03 ASTM 20C	+57 a +65 °C	0.1 °C
B089-04 ASTM 21C	+79 a +87 °C	0.1 °C
B089-05 ASTM 22C	+95 a +103 °C	0.1 °C

B087-11

FILTER FUNNEL complete with wire filter ring mesh.



B087-11

B087-12

B087-12

WITHDRAWAL TUBE complete.

SPARES for SAYBOLT

B089-06 Furol orifice

B089-07 Universal orifice

B089-08 Saybolt flask 60 ml capacity



B086-02

B086 KIT

B087-01 TWO TUBE SAYBOLT VISCOMETER

Basically structured as mod. B087 but with two tubes. Supplied complete except thermometers, filter funnel and withdrawal tube.

Dimensions: 270x270x550 mm approx.

Weight: 14 kg approx.



B087-01